



Euro Offshore.nl

EO WORKBOATS - FIBRE SHARK

Ferry 12.00

Brand: FibreShark Ferry 12.00		Auxiliary equipment:
Model: 12.00 Meter		E-system for 24- and 220 Volt / Marine generator
Catamaran hull type—GRP		Shore power connection.
Building year:	NEW	AC units in cabins
Passenger Ferry	y	Engine room ventilation system.
Optional Approval under MCA.		Freshwater (200 liter tank) Grey / black water tank system.
SPECIFICATIONS:		Amplifier and speakers / Television connection for inboard broadcasting.
Hull:	GRP	Toilet room with sink, also suitable for disabled people.
	butside seating space.	Hydraulic steering .
Dimensions:		Deck layout:
	12.00 m	Deck is with anti slide profile.
Length: I.o.a.:		SS railing in aft, bow and upper area
Beam o.a.:	5.20 m	Cleats for mooring
Draft appox:	1.00 M	Storage on deck and belowdeck.
Capacity :		Mast for navigation lighting, antenna, radar
Fuel:	2 x 1.000 L	Stairway to upper deck. Inside and outside. (optional depending arrangement).
Speed:	To be discussed. Depending regulations.	Nautical and communication equipment:
Crew:	2-3 seats.	Echo sounder, GPS, (Optional Radar, AIS), double VHF Radio.
Passengers:	50 pax depending on arrangement and layout. Client choice.	Optional SART transporder, GMDSS approved
		Optional EPIRB. GMDSS approved
Performance:		Various:
Range: Propulsion sys	Depending engine type tem:	Windows with 8mm toughened front glass and 5mm toughened side glass. All windows are fixed. Optional sliding windows. (depending certification rules).
Engine: 2 x Hyundai inboard diesel (2 x500 HP) with shaft propulsion.		Fire fighting equipment.
Cabin:		Optional search light roof unit with remote control.
Several cabin arrangements possible. Open / half open/ enclosed. Up to 3 crew seating. Complete with steering console.		Optional electrical anchor winch with anchor, chain and line.
		Fire extinguishers.
Captain position is having 360 degree visibility.		Swimming ladder.
Saloon with 50 luxury seating's and excellent visibility. All cabins are fully		Colour and outfitting in agreement with client.
insulated for optimal climate and sound protection.		Approx. delivery time is 10 months.
Sufficient exits doors.		Note: we also have 14—16—24 and 28 meter version.